

10. Specifications

Counting Speed:	3 speeds: 600, 1200 & 1500 notes per minute
Display Type:	LCD 3 digit batch display 4 digit total display
Document Size Limits:	100 × 185 ~ 50 × 90 (mm) 3.95 × 7.28~1.97 × 3.54 (inches)
Input hopper Capacity:	300 circulated notes
Output Stacker Capacity:	150 circulated notes
Batching:	variable 1 to 999 (maximum)
Error Detection:	Double, chain, half-note, jam (standard) Counterfeit suspected, size, width (option)
Counterfeit Detection (option):	Width and Length
Document Feed Mechanism:	Friction, intermittent roller type
Dimensions:	255mm(H) × 280mm(W) × 230mm(D) 10.04"(H) × 11.02"(W) × 9.06"(D)
Net Weight:	7.03Kgs. (15.50 lbs.); shipping: 8.25Kgs. (18.19 lbs.)/unit
Power Source:	120/230 VAC (selected by switch), 50/60 Hz
Power Consumption:	70W (avg.)
Temperature Limits:	Operating : +5°C to +40°C (41°F~104°F) Storage : -20°C to +50°C (-4°F~122°F)
Density Setting:	Adjustable 5 levels
Accessories	
1) Power code	
2) Dust cover	

NOTE

*Specifications and design are subject to change
without prior notice.*
